



Product Overview

GM Texo Compound is a water based acrylic emulsion designed as a mid coat for exterior textured systems. It creates decorative relief finishes while filling minor surface irregularities and undulations.

Key Features

- Uniform Texture: Produces consistent, attractive patterns over large areas.
- Surface Levelling: Hides small cracks, pinholes and unevenness.
- Breathable Film: Allows moisture vapor to escape, reducing blistering risk.
- Reduced VOC: Formulated for 0 g/L VOC (ISO 11890 EU), promoting better air quality.
- Easy Cleanup: Tools flush clean with water immediately after use.

Recommended Uses

- As the intermediate “texture” coat in acrylic exterior wall systems
- Filling and smoothing minor defects on both exterior and interior concrete or plaster
- Decorative relief finishes for façades, feature walls and architectural details

Substrate Compatibility

- Cement plaster
- Rendered masonry
- Concrete panels or blockwork

Physical & Packaging Data

Property	Value
Color	White
Specific Gravity	~1.8 (theoretical)
Volume Solids	62 ± 2 %
VOC Content	0 g/L (ISO 11890 EU)
Packaging	4 L and 18 L containers
Dilution	Up to 10 % water
Theoretical Coverage	6.2–0.31 m ² /L (depending on texture and substrate porosity)

Surface Preparation

- Ensure substrate is sound, clean and thoroughly dry.
- Remove grease, oil, loose paint, curing agents or form release residue.



Primer Coat

- Apply a single coat of GM Acrylic Emulsion Primer or GM Alkali Resistant Primer.

Undercoat (Texture Coat)

- Apply one full coat of GM Texture Compound by hopper gun, roller or trowel.
- Adjust film thickness to achieve desired relief: 100-2000 µm dry.

Topcoat

- Finish with two coats of GM Exterior Topcoat (e.g., GM WeatherShield or GM UVGuard).

Thinning & Cleanup

- Thin with up to 10 % clean water if needed for spraying.
- Clean tools and equipment immediately with water.

Drying & Recoat Intervals (RH 50 %)

Substrate Temp	Touch Dry	Hard Dry	Minimum Recoat
10 °C	20 hours	14 Days	6 Days
23 °C	10 hours	7 Days	3 Days
40 °C	6 hours	4 Days	1 Day

Storage & Handling

- Store in a cool, dry, well ventilated area.
- Keep containers tightly sealed when not in use.
- Shelf life: 12 months unopened at 5-35 °C.

Health & Safety

- Always consult the GM Paints Safety Data Sheet before use.
- Wear suitable personal protective equipment: gloves, eye protection and a dust/mist respirator as required.
- Avoid ingestion, inhalation and skin contact.

Disclaimer

The information presented here is based on laboratory testing and practical experience. Variations in equipment, surface conditions and environmental factors may affect performance. GM Paints makes no other warranty, expressed or implied, regarding this product other than that it meets the published specifications. Users must determine suitability for their own applications.