



## Product Overview

GM Medium Texture is a heavy build coating formulated on an acrylic copolymer base, enriched with specially selected mineral aggregates. Designed for both indoor and outdoor surfaces, it creates a durable, dead flat finish with a sculpted texture that enhances architectural features.

## Key Features

- Robust surface film: Delivers excellent hardness and structural integrity.
- Strong bond: Adheres securely to a wide range of substrates, preventing peeling.
- Weather resistant: Retains performance in sunlight, rain and temperature swings.

## Recommended Applications

Suited for decorative and protective coatings on:

- Concrete
- Plaster
- Brick and blockwork
- Gypsum board
- Asbestos panels
- Wood

## Technical Specifications

Finish:	Ultra-matte
Colour Range:	Standard white plus any shade from GM's colour palette
Density:	Approx. 1.70 kg/L at 25 °C
Consistency:	Thixotropic, heavy-body for pronounced texture
Ignition Rating:	Non-flammable
Volume Solids:	~65 %

## Surface Preparation

- Remove all contaminants: dust, loose particles, oil, grease, efflorescence, mold or mildew (wash affected areas with diluted bleach, then rinse).
- Ensure substrates are fully dry.
- For new concrete, allow a minimum curing period of 30 days and verify moisture content is below 5 %.

## Primer & Texture Application

- Priming: Apply one even coat of GM Primer Sealer. Let dry.
- Texture: Apply GM Medium Texture evenly with a trowel, roller, or spray.
- Adjustment: Ready to use. Add up to 2% water if needed for hot/dry conditions.



## Technical Data Sheet MEDIUM TEXTURE

---

### Tooling Options

- Steel trowel
- Plastic trowel
- Medium nap roller
- Airless spray equipment

### Dry Off Times (at 25 °C, 50 % RH)

- Surface set: ~1 hour
- Safe to handle: ~6 hours
- Full performance: ~24 hours

### Packaging & Storage

- Packaging: 20 kg moisture resistant bags
- Storage: Store sealed containers in a dry, well ventilated area, away from direct heat or sparks. When kept under these conditions, the product remains stable for up to 12 months.

### Safety Precautions

- Keep the container closed when not in use and store it in a cool, airy location, away from ignition sources.
- Maintain good airflow during application; avoid inhaling spray mist or dust.
- Do not eat, drink or smoke while using this product.
- Store all coatings out of reach of children.

### Environmental Guidance

Return any leftover material and empty packaging to authorized recycling or reuse facilities. Dispose of waste in compliance with local environmental laws.

### Disclaimer

Product data is based on controlled tests and field experience. Users should confirm suitability for their specific project by consulting GM Paints technical advisors. Specifications are subject to change without notice.