



Product Overview

GM Exterior Filler is a two-component crack repair compound specially developed to restore surfaces with minor structural gaps and imperfections. Designed with advanced acrylic emulsion technology, it delivers reliable performance for both interior and exterior environments. Suitable for use on concrete, plaster, brick, and masonry surfaces, it ensures a smooth, even base for decorative topcoats.

Key Features

- Repairs cracks up to 1 cm in width and depth
- Strong grip and excellent mechanical strength
- Smooth blending with primers and finish coats
- Matt finish that allows seamless paint coverage
- High resistance to peeling and cracking
- Ideal for harsh exterior conditions

Recommended Applications

Recommended Areas:

- Residential buildings
- Commercial complexes
- Institutional structures
- Walls, ceilings, façades, and concrete panels

Suitable Substrates:

- Cement render
- Concrete
- Plaster Brick and block walls

Technical Specifications

Property	Value
Appearance	Smooth, Matt finish
Color Options	White & Grey
Specific Gravity	Approx. 1.90 ± 0.1
Solids by Volume	$50\% \pm 2\%$
Viscosity	Thick, Paste-like consistency
Max Crack Size	Up to 1 cm (width & depth)

Surface Preparation

- Clear the area of dust, grease, old paint, or loose materials
- For better adhesion, slightly moisten the surface (do not soak)
- Allow dampened surfaces to partially dry before applying



Application Instructions

- Use a stainless-steel putty knife or trowel
- Apply in thin layers, gradually building up to fill deeper cracks
- Ensure each coat is completely dry before reapplication

Drying Time

Process	Time
Surface Dry	2 hours
Recoating Time	Minimum 8 hours
Full Dry	8 hours
Final Curing	24 hours

Thinning

- Ready to use after mixing
- If necessary, a small amount of clean tap water (up to 2%) can be added to adjust the consistency in hot or dry weather conditions.

Tool Cleaning

Rinse tools immediately after use with clean water

Packaging

Available in pre-measured sets:

Powder: 3.8 kg

Liquid: 0.90 kg

Health & Safety

- Wear protective gear during handling and application
- Avoid inhalation of dust or vapors and contact with skin or eyes
- Ensure adequate ventilation during use
- Keep out of reach of children
- Dispose of unused material responsibly, following local environmental regulations